

360L Heated Industrial Ultrasonic Cleaner Ultrasonic Generator For Automatic With CE

Our Product Introduction

for more products please visit us on skymenultrasonic.com

Basic Information

- Place of Origin: China
- Brand Name: skymen
- Certification: CE
- Model Number: JTS-1060
- Minimum Order Quantity: 1
- Price: Negotiation
- Packaging Details: 1pcs / wooden case packing
- Delivery Time: In Stock
- Payment Terms: T/T, Western Union
- Supply Ability: 100 /month




Product Specification

- Material: Stainless Steel SUS304/316L
- Control: Separate Generator
- Optional: Oil Filter System
- Special: Multi Tank
- Application: Degreasing
- Ultrasonic Frequency: 28khz/40khz
- Ultrasonic Power: 3000W
- Heater: 20-80 Adjust
- Power: Adjustable Ultrasonic Power
- Highlight: **automotive ultrasonic cleaner, ultrasonic cleaning device**



More Images



Product Description

360L Heated Industrial Ultrasonic Cleaner Ultrasonic Generator For Automatic With CE

The machine is customized and certified with CE.
If need, rising tank or drying tank is optional based on customer's needs.
Large Capacity for Diesel Particulate Filter Cleaning

Product Description

Model	JP-720G with oil filtration system
Capacity	360 liter
Inner tank size	1000*600*600mm (L*W*H)
Unit size	1170*770*815mm (L*W*H)
Package size	1380*1315*1125mm (L*W*H)
Frequency	40,000Hz
Ultrasonic max power	3600W adjustable
Heating power	9000W
Timer	1~99hours adjustable
Heater	20~80 adjustable
Powe supply	AC 220V, AC 380V, 50/60Hz, 3phase
Tank material	SUS304, 2mm thickness
Shell material	SUS304, 1mm thickness
Others	With drainage, castors, basket, lid
N.W. / G.W.	350KG / 402KG

Features:

1. Tank materail is SUS304, 2mm thickness, Human hand argon welded, Sturdy and durable resistance to high tempearture
2. 50W industrial transducers, outstanding cleaning effects
3. Separate generator controller
4. Power adjustable, choose different power according to different cleaning objects
5. Digital timer: 1~99hours timer adjustable, continious working for long time.
6. Memory function, with memory chip, no need to reset time and temperature every time.
7. 20~80C adjustable, 1500W heating panel, faster cleaning
8. Industry use power cord, more safer.
9. Can bear 300KG cleaning objects
10. Accessories: Machine with separate generator controller, stainless steel basket, drainage, lid, power cord, movable castors etc.

Ultrasonic cleaner applied ranges:

Machinery industry: Removing rust and grease for Machinery Parts, Engine, carburetor and automobile parts cleaning, Filter. Clear filter, especially in the railway industry, for degreasing decontamination conditioned train cars, each member of the front of the train rust, oil, and rust, very suitable

Surface treatment industry: Degreasing derusting before plating, cleaning before Ion plating, Metal workpiece surface activation treatment, phosphating, remove carbon deposition, oxidation and polishing paste

Instrument industry: precision parts cleaning

Electronic industry: remove Rosin and welding spot for p.c.b. boards, machinery parts cleaning

Medical industry: medical apparatus and instruments cleaning and disinfecting

Semiconductor industry: Semiconductor chips etc.

Jewellery & Watch industry: Remove oil sludge, dust, oxidation layer, polishing paste. Etc.

Chemical biology industry: labwares' cleaning and descaling

Optics industry: Optical vessels oil, sweat and dust removal

Textile printing and dyeing industry: textile spindle, spinneret plate cleaning.

Petroleum chemical industry: Metal screen cleaning, chemical containers and switches' cleaning

Others

Description:

Adjustable ultrasonic power
Original BLT type transducer
SUS304/316L tank
Adaptable for continuous operation
Adjustable thermo controller
Adjustable ultrasonic power
With separate control ultrasonic electronic generator
Sweep mode control available
Digital timer control
Boost mode& oil skimmer upon client's requirement
Pressure pump and filter system
With pneumatic lift to up and down goods.

Product Description

Model: Skymen™	JTS-1012	JTS-1018	JTS-1024	JTS-1030	JTS-1036	JTS-1072
L1	355	406	500	500	500	1110

TANK'S WORKING DIMENSION (mm)	W1	305	305	355	406	460	600
	H1	355	460	500	500	550	600
OVERALL DIMENSION (mm)	L2	535	586	680	710	710	1320
	W2	485	485	535	586	640	780
	H2	750	680	720	720	770	820
TANK'S TOTAL CAPACITY		38L	56L	88L	101L	126L	369L
TANK'S MATERIAL	SUS304 / SUS316L						
IN-TANK SURFACE FINISHING	Hard-Cr Plating Treatment (20+ microns)						
HOUSING'S MATERIAL	Stainless steel						
ULTRASONIC FREQUENCY*	28kHz / 40kHz						
ULTRASONIC TRANSDUCER	12	18	24	30	36	72	
ULTRASONIC OUTPUT POWER (MAX.)	600W	900W	1200W	1500W	1800W	3600W	
ELECTRONIC GENERATOR	KG600	KG900	KG1200	KG1500	KG1800	KG3600	
	Build-in		Separate				
HEATER'S (HOT PLATE) POWER	1.5kW	3kW			4.5kW	9KW	

Competitive Advantage:

Material : SUS304/316L with 2mm thickness

15 years experience engineer will design the machine for you

Filtration System: for heavy duty oil removing, cycle cleaning solvent, prevent second pollution and better cleaning effects.

PCB Board: manufactured by Skymer factory, more stable



Package

Packing , loading, delivery time	
Packing unit	1set/wooden case
Packing method	Export wooden case
Loading port	Shenzhen
Delivery time	About 15 working days
Minimum Order Quantity	1set
Transport method	By express company / air / sea



Skymer Technology Corporation Limited

☎ 86-755-27094405

✉ info@skymer.cc

🌐 skymenultrasonic.com

